


Petroglyph catches whispers of time and engraves them on its body. Shallow and deep imprints of history in light or in dark that Petroglyph has rendered fills the building with charm, as humans, who once were clumsy but finally find their inner dexterity, weave with Petroglyph ancient and beautiful stories, leaving their traces you may notice in the silent and mysterious art that does not go astray over thousands of years. The building with Petroglyph is more than just a reinforced concrete structure, where, with a bit of patience, you can hear murmur of history echoes and notice how the trajectory of time reveals.

**INVITAC**  
Module Model



**LINEAR PERFORMANCE WARRANTY**



Glass	Heat Strengthened Glass
Junction Box	IP68 Rated
Output Cables	TUV 1x4.0 mm Customized Length
Maximum System Voltage	1500 VDC (IEC)
Maximum Series Fuse Rating	33 A
Power Tolerance	0-±3 %
Temperature Coefficients of Pmax	-0.35 %/°C
Temperature Coefficients of Voc	-0.29 %/°C
Temperature Coefficients of Isc	0.048 %/°C
Nominal Operating Cell Temperature (NOCT)	45±2 °C
CTM	±3-18 %

- Thickened Double-Layer Tempered Glass
- High Impact Resistance
- 50% Increased High Mechanical Performance Modules
- Optimized Soundproofing Insulation

**Higher Aesthetics**

Inherent advantages of integration in module design, better appearance without metal wire exposition.

**Higher Power Efficiency**

Higher-density cell arrangement can put more cells per unit area and achieve higher module efficiency, meet the requirements for energy-saving buildings.

**Building Integrated Higher Safety**

Double layers of tempered glass to meet the requirements of building safety; with fireproofing, better wind load, heat resistance and frost resistance. Be used as building unit for integrated installation.

