

If buildings can take us to the past, Terracotta is the flexible and reliable clockwork that reverses time. Time flows in silence, but Terracotta on its way to seeking a balance between red brick and embroidered brown with gentleness and simplicity records human vicissitudes as well as architecture evolution, crystalized as human wisdom and the constant core of architecture. This historian still writes pages telling the stories of nature and human and the charm of the ancient past. In those standing buildings, it has lasted for ages.

Module Model



LINEAR PERFORMANCE WARRANTY



15 Year Product Warranty

25 Year Linear Power Warranty 0.55% Annual Degradation Over 25 years

Junction Box	IP68 Rated
Maximum System Voltage	1500 VDC (IEC)
Power Tolerance	0-±3 %
Temperature Coefficients of Voc	-0.29 %/°C
Tectomatum Codificients of tic	
Nominal Operating Cell Temperature (NOCT)	45±2 ℃







Higher Aesthetics

Inherent advantages of integration in module design, better appearance without metal wire expostion.

Higher Power Efficiency

Higher-density cell arrangement can put more cells per unit area and achieve higher moduleefficiency, meet the requirements for energy-saving buildings.

Building Integrated Higher Safety

Double layers of tempered glass to meet the requirements of building safety, with fireproofing, better wind load, heat resistance and frost resistance. Be used as building unit for integrated installation. installation

